




NXT[®] Level Plus

Premium Quality, Fiber Reinforced Underlayment

NEW



Data Sheet 505

NXT[®] Level Plus is a high quality, cement-based, fiber reinforced, free-flowing underlayment for use in leveling interior Plywood/OSB, Gypsum and Concrete substrates. Rapid setting formula produces a flat, smooth and hard surface for the installation of finished flooring as soon as 12 hours.

FEATURES	BENEFITS
Rapid curing	Finish floor goods can be applied 12 hours after placement
Fiber reinforced	Additional flexural strength
Self-leveling	Smooths existing rough concrete, gypsum and plywood/OSB
Pourable and pumpable	From small to larger applications
Can be applied over concrete testing up to RH of 100%	Minimal downtime
Superior compressive strengths	Long lasting application
Equipped with Microban [®]	Prevents mildew growth
Low-shrinkage	Very stable

Suitable Substrates

- Concrete slabs
- Plywood/OSB (no lath required)
- Gypsum

Packaging

55lb (25kg) bag / 56 per pallet

Item

0902-0055-21

Advantages

- LIFETIME System Warranty available
- Can be placed from 1/8" to 1- 1/4" (3 mm to 32 mm)
- Extremely durable
- Suitable surface for most finished floor goods as soon as 12 hours
- 5300 PSI (36.5 MPa) in 28 days
- Walkable in 2 to 3 hours

Uses

- Commercial, retail (malls & shops)
- Healthcare
- Education (schools & universities)
- Residential
- Hospitality, Hotels
- Office

MICROBAN






NXT[®] Level Plus

Contrapiso reforzado con fibra de primera calidad

NUEVO



Especificación 505

NXT[®] Level Plus es un contrapiso de alta calidad y gran fluidez, formulado a base de cemento, reforzado con fibra, que se utiliza para nivelar sustratos interiores de madera contrachapada, de OSB o de yeso. Fórmula de fraguado rápido que produce una superficie plana, lisa y dura para la instalación de revestimientos en tan sólo 12 horas.

CARACTERÍSTICAS	BENEFICIOS
Curado rápido	Los productos para pisos terminados se pueden aplicar 12 horas después de la colocación
Reforzado con fibra	Resistencia adicional a la flexión
Autonivelante	Suaviza hormigones ásperos existente, yeso y madera contrachapado/Fibras Orientadas
Apto para vertido y bombeo	De aplicaciones pequeñas a grandes
Se puede aplicar sobre concreto para pruebas con el 100 % de HR	Tiempo de inactividad mínimo
Resistencia adicional a la flexión	Evita el crecimiento de moho
Contiene el agente Microban [®]	Prevents mildew growth
Bajo nivel de contracción	Muy estable

Sustratos adecuados

- Piso de concreto
- Madera contrachapada/OSB:
No requiere malla de metal
- Yeso

Presentación

Bolsa 25kg (55lb) / 56 por palet

Artículo N.º

0902-0055-21

Ventajas

- Garantía del sistema disponible DE POR VIDA
- Se puede colocar de 3.1 mm a 31.7 mm (1/8" a 1 1/4")
- Extremadamente durable
- Superficie adecuada para la mayoría de revestimientos en tan sólo 12 horas
- 36.5 MPa (5300 PSI) en 28 días
- Se puede pisar entre dos a tres horas

Usos

- Comercial, minorista (centros comerciales y tiendas)
- Atención médica
- Educación (escuelas y universidades)
- Uso residencial
- Alojamiento, hoteless
- Oficinas

